

Technical Datasheet - Metal Trim

Aluminium Pro Trim - ETA

Product Description


Genesis ETA Aluminium Profile offers a perfect quadrant face. Designed to protect the edge of ceramic or similar hard surface in wall or floor installations. Designed with a vertical anchor leg to give the front face more strength. The ETA also has Internal EIQ and External EAC

Corner Pieces providing the perfect three way corner and preventing time consuming mitering and sharp dangerous edges.

Dimensions and Colour

All available in 2.5m lengths in varying depths and finishes - see the Metals colour chart for depth/finish combinations


Range



Technical Details

Profiles are available in different anodised finishes and powder coated finishes - All natural Aluminium (Mill finish) has a oxide film of approx 0.2 microns, when Mechanically and Chemically polished the anodising process increases this to 5 microns, up-to 20 for the Matt finish and 100 for Powder coated.

Aluminium AA 6063 T6 / UNS A96063 anodised to DIN 17611	
Si%	0.2-0.6
Fe%	0.35
Cu%	0.1
Mn%	0.1
Mg%	0.45-0.9
Zn%	0.1
Ti%	0.1
Cr%	0.1
Al	Balance



Maintenance

Genesis ETA does not require any special maintenance. Oxidation films on Aluminium may be removed with a common polishing agent; however, they do reoccur. Damaged anodised finishes may only be repaired by recoating.

Aluminium must be tested to verify its suitability if chemical stresses are anticipated. Cementitious materials, in conjunction with moisture, become alkaline. Since aluminium is sensitive to alkaline substances, exposure to the alkali (depending on the concentration and time of exposure) may result in corrosion (aluminium hydroxide formation). Therefore, it is important to remove adhesive or grout residue from visible surfaces. In addition, ensure that the profile is solidly embedded in the setting material and that all cavities are filled to prevent the collection of alkaline water.

The anodised layer creates a finish that retains a uniform appearance during normal use. The surface, however, is susceptible to scratching and wear and may be damaged by tile adhesive, mortar, or grouting material. Therefore, setting materials must be removed immediately. Otherwise, the description regarding aluminium applies.

Installation

1. Select ETA according to tile thickness.
2. Trowel tile adhesive over the area that forms the perimeter of the tiled covering.
3. Press the perforated anchoring leg of the ETA into the tile adhesive and align, mechanical fix if required
4. Trowel additional adhesive over the perforated anchoring leg to ensure full coverage.
5. Solidly embed the tiles so that the tiled surface is flush with the top of the profile, the profile should not be higher than the tiled surface.
6. Fill the joint completely with grout.

Allied Products

ETA profiles have specially designed external corner pieces EAC and internal corner pieces EIA designed to provide a perfect rounded safe edge when mitering either profile. Available in 6mm, 8mm, 10mm and 12mm depths.

P.V.C. Trim • Stair Nosings • Expansion Joints • Transitions • Seals • Edge Protection • Metal Trim • Skirting • Tools

Tel: +44 (0)1642 713000

Email: info@genesis-gs.com

www.genesis-gs.com

UK Head Office & Factory
Stokesley Business Park Stokesley
North Yorkshire TS9 5JZ UK



Genesis
For the Perfect Finish

